

## E-FLARE SAFETY BEACONS

PRODUCT INFORMATION



# BE SEEN AND BE SAFE

### LAW ENFORCEMENT & EMERGENCY RESPONDERS

- Intensely bright can be seen for ¾ of a mile
- Lightweight and simple to use
- 360° visibility without the risk of fire or explosion



#### PRODUCT DESCRIPTION

#### E-FLARE™ WARNING BEACONS

Our E-flare<sup>™</sup> line of products is not just innovative, they're life savers. They've progressed technology from a torch, to light beacons that use multi-color and sequencing of light that can be seen for over 3/4 of a mile away without the night vision, point fixation and distance judgement problems associated with strobe and incandescent lights.

#### **APPLICATIONS**

Personal Visual Protection

**Location Alert** 

**Traffic Management** 

Accident or Hazardous Scene Alert

Helicopter Landing Zone Demarkation

**Unusual Hazards** 

Obstacle Identification

Vehicle Breakdowns

**Emergency Landing Strip** 



#### ACCESSORIES



Rubber Base Mount Aviation Rubber 939-FFBASE

Magnetic

Mounting Clip

939-FFMAGCLIP



Base Mount 939-EFAVBASE



939-FFCLIP



939-EFMAGBASE

Magnetic Base Mount

Cone Mounting Clip Flotation Collar 939-FFFC01/I

#### PERFORMANCE

#### BE SEEN AND SAFE IN ALMOST ANY SITUATION

Intensely Bright - Patented fresnel lens and high-luminosity LEDs allow beam to be visible for 3/4 mile without the night vision, point fixation, and distance judgment problems associated with strobe and incandescent lights. The florescent body color and reflective strip allow for maximum unit visibilty.

Lightweight and Simple to Use - Beacons now weigh under 2/3 lb. with 4 "AA" batteries installed. An improved switching mechanism involves a simple twist of the lens to the desired function. Place unit(s) to create a highly visible warning and safety zone for people, work areas, hazards and accidents.

Durable - The impact resistant ABS body and shatterproof polycarbonate lens will survive a 3-foot drop onto a concrete surface, and are both waterproof (up to 100 feet) and dustproof.

Double the Safety - Beacons provide safety by ensuring maximum 360° visibility, but, unlike pyrotechnic flares, there is no risk of fire or explosion, and no toxic fumes or residue.

Infinitely Versatile - High-strength clips with added holes for versatility of attachment to belts, clothing, vehicles, traffic cones or signs.

HAZMAT accredited for use in Class 1, Division 2 / Zone 2 hazardous areas.

ITEM Number	BEACON COLOR	LIGHT INTENSITY	OPERATION	FLASH RATE (FPM)	HEIGHT	WEIGHT (WITH BATTERIES)
939-AT290-R	Red	8 LED	Flash or Steady-On 1-Color	165-185	8"	0.65 lbs
939-AT290-A	Amber	8 LED	Flash or Steady-On 1-Color	165-185	8"	0.65 lbs
939-AT290-B	■Blue	8 LED	Flash or Steady-On 1-Color	165-185	8"	0.65 lbs
939-AT290-G	Green	8 LED	Flash or Steady-On 1-Color	165-185	8"	0.65 lbs
939-AT290-W	□White	8 LED	Flash or Steady-On 1-Color	165-185	8"	0.65 lbs
939-AT293-R/B	Red & Blue	4 + 4 LED	Dual Flash 2-Color	165-185	8"	0.65 lbs
939-AT293-A/W	Amber & White	4 + 4 LED	Dual Flash 2-Color	165-185	8"	0.65 lbs
939-AT293-B/W	■ Blue & White	4 + 4 LED	Dual Flash 2-Color	165-185	8"	0.65 lbs
939-AT293-R/A	Red & Amber	4 + 4 LED	Dual Flash 2-Color	165-185	8"	0.65 lbs
939-AT293-R/W	■ Red & White	4 + 4 LED	Dual Flash 2-Color	165-185	8"	0.65 lbs
939-AT280-R	Red	8 LED	Flash or Steady-On 1-Color	165-185	6"	0.55 lbs
939-AT280-A	■ Amber	8 LED	Flash or Steady-On 1-Color	165-185	6"	0.55 lbs

#### LIMITED WARRANTY AND DISCLAIMER OF IMPLIED WARRANTIES:

PIP, Inc. warrants only that PIP products will be free from defects in materials and workmanship at the time of sale. Any claim not timely made shall be waived. This limited warranty is exclusive and in lieu of all other warranties, express, implied or statutory. The exclusive remedy shall be limited to replacement of the defective product or purchase price refund, at PIP's option. All implied warranties which may arise by implication of law or application, course of dealing, usage of trade, including, but not limited to, implied warranties of merchantability, fitness for a particular purpose, title, and non-infringement are expressly excluded.

