

## TEST REPORT





Page 1/3

21 October 2020

3F, Building Block 2, No. 3400 Gonghexin Road, Jing'an District - Shanghai 200436, P.R. CHINA 上海市静安区共和新路3400号2幢3层

Tél.: +86 21 68 55 50 32 Fax: +86 21 68 55 50 33 E-mail: ctcshanghai@ctcgroupe.com

june. guo@pipchinaltd. com

Report No.: S201010849\_1

APPLICANT: PROTECTIVE INDUSTRIAL PRODUCTS HONG

KONG LTD., (C06226)

FLAT 1-11,

6/F KAR WAH INDUSTRIAL BUILDING

8 LEUNG YIP STREET . YUEN LONG, N. T

HONG KONG

Date of receipt :20 Oct. 2020 :21 Oct. 2020 Testing period

:21 Oct. 2020

Buyer: --

Style / Article no. :16-VRX380

Test(s) requested

Service :SHUTTLE

Brand / Section

Season End use

Factory name

Factory code

For CE Marking: Yes

Previous report

Product category Product type

:FIRST TEST Test stage

Supplier name Exported to

#### 1. Conclusion:

	<u>Tests description</u>	<u>Conformity</u>
	ANSI-ISEA 105: 2016	
1	Cutting resistance TDM	Level A3

Pass: requirements met Fail: requirements not met None: no requirement for this test N/A: not applicable

Approved by

Henry YAN Laboratory Manager



## **TEST REPORT**





Page 2/3

Report No.: S201010849\_1

21 October 2020

APPLICANT: PROTECTIVE INDUSTRIAL PRODUCTS HONG

KONG LTD., (C06226)

### 2. Sample(s) description assigned by laboratory:

Size Analyzed product Description Sample information

GLOVE

black PU(HPPE(high performance polyethylene)/nylon/spandex)
palm



201010849



## **TEST REPORT**





Page 3/3

Report No.: S201010849\_1

21 October 2020

APPLICANT: PROTECTIVE INDUSTRIAL PRODUCTS HONG

KONG LTD., (C06226)

#### 3. GLOVE/

black PU(HPPE(high performance polyethylene)/nylon/spandex) palm

	Method	Client Requirement	Unit	Result	Conformity
(+) 5.1.1. Cutting resistance TDM	ASTM F2992 /F2992M - 15				
Correction factor of the sharp edge of the blade with the neoprene				0.98	
Load for a distance of 20 mm cut			g	1381	
Performance level				Level A3	

# END OF TEST REPORT Classification Table for Cut Resistance (ANSI-ISEA 105)

Level	Weight (grams) needed to cut through material with 20 mm of blade travel			
A1	>=200			
A2	>=500			
A3	>=1000			
A4	>=1500			
A5	>=2200			
A6	>=3000			
A7	>=4000			
A8	>=5000			
A9	>=6000			