



NOVAX®

Class 2 Rubber Insulating Glove with Straight Cuff - 14"

- Contoured shape reduces hand fatigue
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- Silicone free
- Individually numbered for traceability and stamped with factory manufacturing date
- Meets ANSI/ASTM D120 standard.

Applications

- Power Generation
- Electrical Contractors
- Plant Maintenance
- Utility Work
- Hybrid Automotive Repair, Service and Manufacturing

Technical Data

| | |
|----------------------|--------------------------|
| Color | Black |
| Sizes Available | -- |
| Packaging | Boxed |
| Packed | 12/Case |
| Case Dimensions (cm) | 43.00 x 43.00 x 50.30 |
| Case Weight (kg) | 9.58 |
| Country of Origin | Malaysia |
| Material | Rubber |
| Length | 14" |
| Cuff | Straight |
| Cuff Color | Black |
| Construction | -- |
| Certifications | ASTM D120, Silicone Free |

Performance Data

| | |
|------------------|---------|
| Electrical Class | Class 2 |
|------------------|---------|

Care Instructions

Wash in warm water (29°C/85°F) with mild detergent and disinfect with a small amount of chlorine bleach. Air or tumble dry at low heat (74°C/165°F). Gloves may be dusted lightly with talc to reduce tackiness. Gloves should be stored in a glove bag, finger tips up, hung and not laid flat. Leather protecting glove should be removed before storage. Never fold gloves. Store in as dry and cool (35°C/95°F maximum) location as possible, away from sources of ozone and direct sunlight.