

SPECIFICATION SHEET STYLE: 16-X540



G-Tek[®] PolyKor[®] Xrystal[®] Seamless Knit PolyKor[®] Xrystal[®] Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- · Seamless construction offers increased comfort and breathability
- PolyKor® Xrystal® is a super tough, durable, cut resistant fiber
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light
- 100% Silicone Free

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



Technical Data

| Color | Gray |
|----------------------|--------------------------|
| Sizes Available | |
| Packaging | Pair Bagged Retail Ready |
| Packed | |
| Case Dimensions (cm) | 38.00 x 31.00 x 27.00 |
| Case Weight (kg) | 6.80 |
| Country of Origin | China |
| Liner Material | PolyKor Xrystal |
| Coating | Polyurethane |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | 21 CFR, Silicone Free |

Performance Data

| Cut Level | A4 |
|---------------------------------|--------|
| ANSI Abrasion Level | 3 |
| ANSI Puncture Level | |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4542DX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU® AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-02