



SPECIFICATION SHEET

STYLE: 205-300FR



Base35FR™

Premium Two-Piece 48" Treated Raincoat - 0.35 mm

- Made with .35mm thick treated PVC and polyester fabric
- Self material collar for easy cleaning
- Cape Vented Back
- Underarm Vent
- Not designed for use in an ARC flash or flash fire application
- Limited flammability - Tested in accordance with ASTM D6413
- Silicone free

Applications

- Road Work
- Municipal
- Shipyards
- Railyard
- Agriculture
- Plant Maintenance

Technical Data

Color	Yellow
Sizes Available	--
Packaging	Bagged Each
Packed	10/Case
Case Dimensions (cm)	26.00 x 27.00 x 21.00
Case Weight (kg)	12.00
Country of Origin	China
Fabric	Polyester, PVC
Thickness	0.35 mm
Total Pockets	2
Pocket Type	Flap Pocket
Hood	Detachable
Length	48"
Closure	Snap
Construction	Underarm Vents, Cape Vented Back, Reinforced Wear Points
Certifications	Silicone Free

Care Instructions



Do Not Wash

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-07