



Technical Data

Color	Gray
Packaging	Bulk Pack
Case Dimensions (cm)	45.70 x 30.38 x 22.86
Case Weight (kg)	10.09
Country of Origin	United States
Liner Material	HPPE, Stainless Steel Wire, Dyneema
Top of Arm	Elastic Ends, Elastic Cuff
Finger & Thumb	Thumb Hole
Ply	Single-Ply
Construction	Seamless Knit, Blousy
Certifications	Silicone Free, TAA Compliant

Performance Data

Cut Level A5

Claw Cover®

Seamless Knit HPPE Steel/Spun Dyneema Sleeve with Elastic Cuff and Opening - 100% Silicone Free

- Raises the standards for performance knit sleeves offering an increase in overall performance and value compared to UHMPE sleeves
- Superior cut resistance, up to two times better compared with UHMPE sleeves
- Manufactured with Proprietary HPPE and Stainless Steel and also featuring Spun DSM Dyneema® with Polyester lining
- Superior abrasion and Fatigue Resistance, more than 3 times greater than traditional para-aramid sleeves for lower cost per use
- Exceptional comfort and fit
- Superior washability, can be washed repeatedly in Chlorine Bleach and caustic detergents to remove dirt, odor, grease, oil, and bacteria without degradation, shrinkage, or stiffening. Will retain its performance after multiple washings

Care Instructions



Applications

- High Tensile Strength, Extremely Flexible and Breathable
- Industrial Applications
- Food Processing

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PIP GLOBAL SAFETY | PROTECTION EMPOWERED™

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2026-07-02