



### ATG® MaxiFlex® Active

Seamless Knit Nylon Glove with Ultra Lightweight Nitrile Coated MicroFoam Grip on Palm & Fingers - Touchscreen

- MicroFoam Nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- Silicone and Latex free
- 360° Breathability - Patented micro-foam nitrile coating offers 360° breathability, making it the most breathable glove on the market today
- 25% Thinner - Than most foam nitrile gloves on the market while offering twice the mechanical performance
- Form, Fit and Feel - Mimics the "hand at rest", reducing hand fatigue and increasing comfort

### Applications

- Maximum Breathability, Comfort and Durability
- Light Maintenance and Repair
- Quality Control and Inspection



### Technical Data

|                      |  |
|----------------------|--|
| Color                | Pink   |
| Sizes Available      | --   |
| Packaging            | Bulk Pack                                    |
| Packed               | --   |
| Case Dimensions (cm) | 50.00 x 29.50 x 27.00                        |
| Case Weight (kg)     | 5.00   |
| Country of Origin    | Sri Lanka                                    |
| Liner Material       | Nylon, Spandex                               |
| Coating              | Nitrile                                      |
| Coating Color        | Pink   |
| Coating Coverage     | Palm & Fingers                               |
| Grip                 | MicroFoam                                    |
| Gauge                | 15   |
| Cuff                 | Knit Wrist                                   |
| Impact Protection    | --   |
| Construction         | Coated Seamless Knit, Touchscreen Compatible |
| Certifications       | Silicone Free, Latex Free                    |

### Performance Data

|                     |       |
|---------------------|-------|
| ANSI Abrasion Level | 3     |
| ANSI Puncture Level | 2     |
| ANSI Impact Level   | --    |
| EN 388              | 4131X |
| EN 407              | --    |

### Care Instructions

