

SPECIFICATION SHEET

STYLE: 19-D324



G-Tek® ECO Series™

Seamless Knit Dyneema® Phoenix Blended Glove with Polyurethane Coated Flat Grip on Palm & **Fingers**

- · Seamless construction offers increased comfort and breathability
- Spun Dyneema® Phoenix & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Bio-Based Dyneema fiber provides same performance & protection, while providing lower carbon footprint
- Dyneema® bio-based fibers equates to 450g of CO2 emissions reduction per pair when compared to traditional Dyneema® fibers
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



Technical Data

| Color | White |
|----------------------|--------------------------|
| Sizes Available | |
| Packaging | Pair Bagged Retail Ready |
| Packed | |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00 |
| Case Weight (kg) | 4.90 |
| Country of Origin | Viet Nam |
| Liner Material | Dyneema Phoenix |
| Coating | Polyurethane |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | |

Performance Data

| Cut Level | A2 |
|---------------------------------|--------|
| ANSI Abrasion Level | 3 |
| ANSI Puncture Level | 3 |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4X42BX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

KEY: Made from recycled or bio-based Launderable & Recyclable via TerraCycle®