

# SPECIFICATION SHEET

STYLE: 16-665



### G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell with Aramid PolyKor® is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance while providing protection in heat resistant applications, where sparks and heat are present
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- 100% Silicone Free

## **Applications**

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



#### **Technical Data**

| Color                | Green                    |
|----------------------|--------------------------|
| Sizes Available      |                          |
| Packaging            | Pair Bagged Retail Ready |
| Packed               |                          |
| Case Dimensions (cm) | 38.00 x 31.00 x 27.00    |
| Case Weight (kg)     | 4.00                     |
| Country of Origin    | China                    |
| Liner Material       | PolyKor, Aramid          |
| Coating              | Polyurethane             |
| Coating Color        | Black                    |
| Coating Coverage     | Palm & Fingers           |
| Grip                 | Flat                     |
| Gauge                | 13                       |
| Cuff                 | Knit Wrist               |
| Impact Protection    |                          |
| Construction         | Coated Seamless Knit     |
| Certifications       | Silicone Free            |

#### Performance Data

| Cut Level                       | A5     |
|---------------------------------|--------|
| ANSI Abrasion Level             | 3      |
| ANSI Puncture Level             | 3      |
| ANSI Impact Level               |        |
| ANSI Contact Heat Level         |        |
| EN 388                          | 4X42EX |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |

### **Care Instructions**









