

SPECIFICATION SHEET

STYLE: 647530



Technical Data

Color	
Sizes Available	
Packaging	
Packed	
Case Dimensions (cm)	
Case Weight (kg)	0.00
Country of Origin	China
Material	Microfiber
Outsole	
Тое Туре	
Tread Pattern	
Height	
Construction	
Certifications	

Performance Data

ASTM F2413 Requirement

Care Instructions



Albatros®

Jetstream Impulse LOW S1 ESD HRO SRA Composite Toe Electrostatic Dissipative Shoes, Heat Resistant, Slip Resistant, Safety Boots

- DUAL IMPULSE SLIP RESISTANT OUTSOLE The easy to clean rubber outsole ensures perfect ground contact. It is non-slip and abrasion resistant as well as heat resistant up to 300°C (HRO). The specially designed cleat profile and the wide flex grooves guarantee optimum flexion, optimize the water-displacing properties (windscreen wiper effect) and provide firm grip on a wide variety of grounds.
- IMPULSE.FOAM® midsole Ultimate comfort during long working days. The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. Thereby the IMPULSE.FOAM® does not only return the energy, but also provides maximum cushioning and excellent stability.
- comfit* AIR FOOTBED The newly developed, breathable
 ALBATROS* comfit* AIR footbed has elevations in the heel and ball
 area of the foot as well as a support of the longitudinal arch. This
 helps the foot keeping its natural position in the shoe and stimulates
 the musculature while walking. The slip-resistant textile cover is
 odour-resistant, moisture absorbing and washable at 30°C.
- FAP* Flexible Anti Perforation The flexible anti-perforation midsole made of ceramic-coated fibers, reliably protects the feet completely from penetrating objects.